



## Stainless steel bearing equipment Co....



24096YMBW33W45 Bearing 2D drawings and 3D CAD models

### 24096YMBW33W45 TIMKEN Full Complement Cylindrical Roller Radial Bearings

Bearing No. 24096YMBW33W45

Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	281.076
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Inch - Metric	Metric
Long Description	480MM Straight Bore; 700MM Outside Diameter; 218MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080



## Stainless steel bearing equipment Co....

Noun	Bearing
Keyword String	Spherical
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Manufacturer Item Number	24096 YMBW33W45
Weight / LBS	614
B	8.583 Inch   218 Millimeter
D	27.559 Inch   700 Millimeter
Adapter Part Number	Not Applicable Inch   Not Applicable Millimeter
d	18.898 Inch   480 Millimeter
Design Unit	METRIC
Bearing Weight	282.100 Kg
Cage Type	YMB
UPC Code	087796188341
d - Bore	480.000 mm
D - Outer Diameter	700.000 mm
B - Inner Ring Width	218 mm
B - Outer Ring Width	218.000 mm
R - Inner Ring To Clear Radius <sup>1</sup>	5.000 mm
r - Outer Ring To Clear Radius <sup>2</sup>	5.000 mm
da - Inner Ring Backing Diameter	526.000 mm
Da - Outer Ring Backing Diameter	652.000 mm
C0 - Static Radial Rating	10900000 N
C1(2) - Dynamic Radial Rating (Two-Rows)	5450000 N
e - ISO Factor <sup>3</sup>	0.28
Y0 - ISO Factor <sup>4</sup>	2.45
Y1 - ISO Factor <sup>5</sup>	3.64
Y2 - ISO Factor <sup>6</sup>	2.39
Reference Thermal Speed	370



## Stainless steel bearing equipment Co....

Rating (Grease)	
Reference Thermal Speed Rating (Oil) <sup>7</sup>	410
Cg - Geometry Factor <sup>8</sup>	0.1012